

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2004-020626

(43)Date of publication of application : 22.01.2004

(51)Int.Cl.

G02B 5/30
 B29C 55/02
 G02F 1/1335
 G02F 1/13363
 // B29L 11:00

(21)Application number : 2002-171824

(71)Applicant : FUJI PHOTO FILM CO LTD

(22)Date of filing : 12.06.2002

(72)Inventor : HASHIMOTO NARIKAZU
 KOSEKI KEISUKE
 KAWANISHI HIROYUKI


(54) POLARIZING PLATE AND IMAGE DISPLAY DEVICE

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent large changes in optical properties of a retardation plate attached to a polarizing plate even when the polarizing plate is left to stand under high-temperature and dry conditions.

SOLUTION: The polarizing plate has the retardation plate having optical anisotropy, a first transparent protective film, a linearly polarizing film, and a second transparent protective film in this order, or has the retardation plate having optical anisotropy also acting as a first transparent protective film, a linearly polarizing film and a second transparent protective film in this order.

The polarizing plate is controlled in such a manner that the retardation of the retardation plate measured at 550 nm wavelength changes by less than 15 nm under the conditions: first, the retardation is measured while the polarizing plate is in a controlled environment of temperature and humidity at 25°C and 60% RH(relative humidity), and then the polarizing plate is stored in an environment at 60°C and 10% RH for 3 hours before the retardation is measured.



LEGAL STATUS

[Date of request for examination] 28.01.2005

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]